

## Pendiro CP 300

Article number: 81110032

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 6870 lm  |
| System power         | 47 W     |
| Luminaire Efficiency | 130 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Swivel angle              | +25° / -25°  |
| Weight                    | 3.2 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire shade die-cast aluminium, powder-coated, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |            |
|-------|------|------------|
| 1.0 m | 0.36 | 32522.0    |
| 2.0 m | 0.72 | 8131.0     |
| 3.0 m | 1.08 | 3614.0     |
| 4.0 m | 1.44 | 2033.0     |
| 5.0 m | 1.80 | 1301.0     |
| Ø (m) |      | E0(0°)(lx) |

