

Pendiro EC 125

Article number: 81000149

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 3480 lm |
| System power | 34 W |
| Luminaire Efficiency | 104 lm/W |
| Reflector | Flood |
| Beam angle | 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Illuminance E0(0°) [lx] |
|------------|-------------------|-------------------------|
| 1.0 m | 0.73 | 6909.9 |
| 2.0 m | 1.46 | 1727.5 |
| 3.0 m | 2.19 | 767.8 |
| 4.0 m | 2.92 | 431.9 |
| 5.0 m | 3.65 | 276.4 |

