

## Pendiro EC 125

Article number: 81000212

### LIGHT TECHNOLOGY

LED	COB
Light colour	840
Luminous flux	5150 lm
System power	41 W
Luminaire Efficiency	125 lm/W
Reflector	Flood
Beam angle	40°

### LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratowhite

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.73	10225.8
2.0 m	1.46	2556.5
3.0 m	2.19	1136.2
4.0 m	2.92	639.1
5.0 m	3.65	409.0
	Ø (m)	E0(0°) [lx]

