

# Pendiro EC 125

Article number: 81010130

## LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | GoldenBread |
| Luminous flux        | 2490 lm     |
| System power         | 23 W        |
| Luminaire Efficiency | 108 lm/W    |
| Reflector            | OvalBasic   |
| Beam angle           | 60° x 40°   |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 3.0 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratowhite |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 3924.0 |
| 2.0 m | 2.10 0.82   | 981.0  |
| 3.0 m | 3.15 1.22   | 436.0  |
| 4.0 m | 4.20 1.63   | 245.3  |
| 5.0 m | 5.25 2.04   | 157.0  |
| Ø (m) | E0(0°) [lx] |        |

