

Pendiro EC 125

Article number: 81020122

LIGHT TECHNOLOGY


| | |
|----------------------|-------------|
| LED | COB |
| Light colour | SpecialMeat |
| Luminous flux | 1440 lm |
| System power | 23 W |
| Luminaire Efficiency | 62 lm/W |
| Reflector | Spot |
| Beam angle | 20° |

LUMINAIRE

| | |
|---------------------------|--------------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratosilver |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.31 | 8696.7 |
| 2.0 m | 0.62 | 2174.2 |
| 3.0 m | 0.93 | 966.3 |
| 4.0 m | 1.24 | 543.5 |
| 5.0 m | 1.55 | 347.9 |
| Ø (m) | | E0(0°) [lx] |

