

Pendiro EC 125

Article number: 81040301

LIGHT TECHNOLOGY

| | |
|----------------------|--------------|
| LED | COB |
| Light colour | Fish-Seafood |
| Luminous flux | 2670 lm |
| System power | 41 W |
| Luminaire Efficiency | 65 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-----------|------------|
| 1.0 m | 1.13 0.71 | 3766.0 |
| 2.0 m | 2.26 1.42 | 942.0 |
| 3.0 m | 3.39 2.13 | 419.0 |
| 4.0 m | 4.52 2.84 | 236.0 |
| 5.0 m | 5.65 3.55 | 151.0 |
| | Ø (m) | E0(0°)(lx) |

