

# Pendiro EC 125

Article number: 81050172

## LIGHT TECHNOLOGY


LED	COB
Light colour	Sun
Luminous flux	1660 lm
System power	23 W
Luminaire Efficiency	72 lm/W
Reflector	Spot
Beam angle	20°

## LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratosilver

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.36	7149.0
2.0 m	0.72	1788.0
3.0 m	1.08	795.0
4.0 m	1.44	447.0
5.0 m	1.80	286.0
Ø (m)		E0(0°)(lx)

