

# Pendiro EC 125

Article number: 81060305

## LIGHT TECHNOLOGY



LED	COB
Light colour	GoldenBread
Luminous flux	4120 lm
System power	41 W
Luminaire Efficiency	100 lm/W
Reflector	Flood
Beam angle	40°

## LUMINAIRE

Weight	2.7 kg
Protection rating . class	IP 20 . III
Luminaire colour	stratoblack

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack, separate driver unit

76500037 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.73	7882.8
2.0 m	1.46	1970.7
3.0 m	2.19	875.9
4.0 m	2.92	492.7
5.0 m	3.65	315.3
Ø (m)		E0(0°) [lx]

