

## Pendiro EC 125

Article number: 81070101

### LIGHT TECHNOLOGY

|                      |              |
|----------------------|--------------|
| LED                  | COB          |
| Light colour         | Fish-Seafood |
| Luminous flux        | 1700 lm      |
| System power         | 23 W         |
| Luminaire Efficiency | 73 lm/W      |
| Reflector            | OvalBasic    |
| Beam angle           | 60° x 40°    |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 2.7 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratoblack |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack, separate driver unit

76500034 driver unit, Fix Current, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

