BÄRO
Retail
Lighting

# Pendiro XR

Article number: 80800020

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 1120 lm |
| System power | 15 W |
| Luminaire Efficiency | 75 lm/W |
| Reflector | NarrowSpot |
| Beam angle | 10° |

## LUMINAIRE

| | |
|---|---|
| Weight | 0.6 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratosilver |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry (only luminaire head and holding arm, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®,segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, stratosilver, separate driver unit

76500050 driver unit, Fix Current,
220-240 V / 50-60 Hz, 400 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500051 driver unit, DALI,
220-240 V / 50-60 Hz, 400 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.